



Rep	Details of components	Dia.mm	Characteristics
1	60 × 0.5mm ² in Flexible Tinned copper conductors. (0.18mm/20)	0.93	<p><u>Electrical characteristics</u></p> <p>Operating voltage : 300V 0.5mm² conductors linear resistance : Max 36.8 Ω/Km Insulation resistance : above 200MΩ.Km Test Voltage : 2,000 Volts/1min.</p>
2	Insulation : Teflon FEP Thickness 0.3mm. Numbered WH, BK, R each 20 cores.	1.53	
3	Inner filler for cable round structure.		
4	Assembled binder tape : Al/mylar	14.0	<p><u>General characteristics</u></p> <p>Operating temperature : -60~150℃(peak 200℃) Outside Diameter : 16.2 ± 0.5mm Conductor Strands : per IEC-60228, Class 5 Standard Sheath color : Black(Optional)</p>
5	Tinned Copper braiding shield for noise protection : 0.16mm	14.7	
6	Outer sheath : Teflon FEP Thickness : Nor 0.75mm	16.2	

This Document belongs to "ZEUS ELECTRIC" and can not be used without his authorization.

D					
C					
B					
A	2018.07.19	Creation			SB, Lee
Revision	Date	Contents of Revision	Revised by	Verified by	Approved by